IN THE CLAIMS:

Substitute the following claims for the pending claims having the same numbers.

1. (currently amended) A cable duct device, comprising:

a swellable packer of the kind in which the packer is adapted for sealing an annulus, the packer including a seal material which swells and thereby increases in volume in response to contact with a swell-activating material; and

at least one through-going opening provided in the packer and adapted to constitute a duct for a cable or pipe; and

a slit extending between the through-going opening and an outer surface of the packer prior to actuation of the packer.

- 2. (previously presented) The device according to claim 1, wherein the through-going opening encloses the cable both prior to and after swelling has occurred in the swellable packer.
- 3. (previously presented) The device according to claim 1, wherein the through-going opening has a variable longitudinal extension.
- 4. (previously presented) The device according to claim 1, wherein the through-going opening has a variable cross-section.
 - 5. (canceled)

- 6. (currently amended) A cable duct device, comprising:
- a swellable packer adapted for sealing an annulus, the packer including a seal material which swells and thereby increases in volume in response to contact with a swell-activating material;
- at least one through-going opening provided in the packer and adapted to constitute a duct for a cable or pipe; and
- a slit extending at least partially laterally through a sidewall between the through-going opening and an outer surface of the packer prior to actuation of the packer; and
 - a cable positioned in the packer proximate the slit.
- 7. (currently amended) The device of claim 6, wherein the packer seals about the <u>a</u> cable <u>positioned</u> in the through-going opening when the <u>seal material swells</u> packer is actuated.
- 8. (currently amended) The device of claim 6, wherein the packer is annular shaped and extends lengthwise in a longitudinal direction, wherein the slit through-going opening extends longitudinally through the packer, and wherein the a cable extends longitudinally through the slit through-going opening.
 - 9. (canceled)
- 10. (currently amended) The device of claim 6, wherein the slit intersects an opening extending longitudinally through the

packer, and wherein the <u>a</u> cable is <u>inserted through the slit and</u> positioned in the through-going opening.

11. (currently amended) A method of extending a cable longitudinally through a packer, the method comprising the steps of:

providing a swellable packer including a seal material having an opening extending longitudinally through the seal material, and a longitudinal slit extending between the opening and an external surface of the packer prior to actuation of the packer;

inserting the cable into the opening through the slit; and then swelling the seal material by contacting the seal material with a swell-activating material, thereby causing the seal material to seal about the cable in the opening.

- 12. (previously presented) The method of claim 11, wherein the swell-activating material comprises water.
- 13. (previously presented) The method of claim 11, wherein the swell-activating material comprises hydrocarbons.
- 14. (new) The device of claim 6, wherein the packer comprises a swellable packer including a seal material which swells and thereby increases in volume in response to contact with a swell-activating material.